

Wet Abrasion Scrub Tester

Paint often become soiled especially near doorways, windows, and in work and play areas. Coated surfaces need to be tested for resistance to abrasion caused by a brush, sponge, or other means. The Wet Abrasion Scrub Tester can produce a repeatable, controlled condition to simulate everyday use or wear patterns.

BGD 526 Wet Abrasion Scrub Tester is the newest machine which is developed by Biuged . It can examine washability and related properties that affect the stain resistance of coatings. Detergent performance testing can also be determined in a reproducible manner.

It accords with standards such as ASTM D2486、ASTM D 3450、ASTM D 4213、ASTM D 4828、DIN EN 11330、EN. ISO 11998 etc.

Feature:


- ◆ Running speed can be set to meet requirements of different standards.
- ◆ With four-digit counter, start the machine and it will automatically be stopped when reaching set times.
- ◆ Compatible with a variety of abrasion pads to comply with different standards requirements, such as ISO, ASTM, DIN etc..
- ◆ Quickly and easily to load and unload testing samples and replacing abrasion head.
- ◆ Can work normally under different voltage and frequency
- ◆ With stable and uniform running speed because of Push-rod design
- ◆ Features two brush holders for side by side testing
- ◆ Long service life with hard and durable design
- ◆ The whole machine body is made of anodized aluminum, having stable working status, repeatable test results, no exception even in the fastest speed of the stroke
- ◆ With peristaltic pump design,Control Scrub medium flow accatately.




Wet Abrasion Scrub Tester



Nylon brush of ASTM 2486



ISO 1998 Special brush



Sponges of ASTM D 3450,
ASTM D 4213、ASTM D 4828



Black plastic panel

Main Technical Parameters:

- ★ Specification of brush: Nylon brush bristles in 5/4 pattern extending 19 mm from block.
- ★ Weight of brush (including device holding brush) : 454 ± 10 g (ASTM D 2486) ; 135 ± 1g (ISO 11998)
- ★ Stroke Length: 300mm
- ★ Frequency of travel : 5 ~ 95 times/min (adjustable)
- ★ Range of count: 9999 times
- ★ Size of test plate: 430 × 150 × 0.03mm
- ★ Power of motor: 25W
- ★ Power: 110V ~ 220V; 50/60 Hz
- ★ Overall size: 500 × 460 × 280mm
- ★ Capacity of Water Container: 5L

Ordering Information:

- BGD 526/1---Wet Abrasion Scrub Tester (ASTM D 2486)
- BGD 526/2---Wet Abrasion Scrub Tester (ISO 11998)
- BGD 526/3---Wet Abrasion Scrub Tester (ASTM D 3450)
- BGD 526/4---Wet Abrasion Scrub Tester (ASTM D 4213)
- BGD 526/5---Wet Abrasion Scrub Tester (ASTM D 4828)
- BGD 526/6---Wet Abrasion Scrub Tester (DIN 53778)
- BGD 527---Wet Abrasion Scrub Tester (ASTM D 2486& ISO 11998)

Optional Accessories

- BGD 1045---Abrasive pad (3M Scotch Brite® handpads) (ISO 11998; Size--- 90 × 39mm; Pack of 50)
- BGD 1364---Special nylon brush (ASTM D 2486; 1 pair)
- BGD 1365---Hog Bristle Brush (1 pair)
- BGD 1510---Sponges (ASTM D 3450;1 pair)
- BGD 1511---Sponges (ASTM D 4213;1 pair)
- BGD 1512---Sponges (ASTM D 4828;1 pair)
- BGD 2355---Brass Shim (432 × 12.7 × 0.25mm; 1 pair)
- BGD 2208---Black Plastic Panel (432 × 165 × 0.25mm;pack of 100)